

WAAS CH 61007 W31A	APP CRS 315°	Rwy Idg TDZE 1423 Apt Elev 1425	5099
--	------------------------	---	-------------

RNAV (GPS) RWY 31

CHANDLER FLD (A.X.N)

Inoperative table does not apply to LPV & LNAV/VNAV Cats A/B/C and LNAV Cat C. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 46°C (114°F). DME/DME RNP -0.3 NA. VDP and Baro-VNAV NA when using Glenwood altimeter setting. When local altimeter setting not received, use Glenwood altimeter setting and increase all DAs/MDAs 40 feet and increase LPV and LNAV/VNAV visibilities ¼ mile all Cats.

ODALS

MISSED APPROACH: Climb to 3500 direct OCIWE and via 352° track to TILER and hold.

ASOS 118.375	MINNEAPOLIS CENTER 126.1 269.2	UNICOM 123.0 (CTAF) 0
------------------------	--	---------------------------------

MISSED APCH FIX

122°

TILER

4 NM

302°

OCIWE

Δ 1919

Δ 1607

RW31

1615

30 NM to YIMCU

135°

045°

3600

YIMCU

30 NM to ZECWO

135°

226°

3600

ZECWO

(FAF) UNRUY

3000

135°

226°

3600 NoPT

(IAF) ZECWO

WUNYE

226°

3600

30 NM to WUNYE (NoPT)

045°

2545

315°

4 NM

3600 NoPT

(IF/IAF) WUNYE

045°

3600

(IAF) YIMCU

ELEV 1425

TDZE 1423

3500

OCIWE

tr 352°

TILER

WUNYE

4 NM Holding Pattern

*LNAV only.

*1.3 NM to RW31

UNRUY

315°

135°

3600

GP 3.00°

TCH 49

1.3 NM

4.4 NM

6.2 NM

REIL Rws 4, 13, and 22

MIRL Rws 4-22 and 13-31

CATEGORY	A	B	C	D
LPV DA	1815-1¼		392 (400-1¼)	
LNAV/VNAV DA	1885-1½		462 (500-1½)	
LNAV MDA	1880-¾	457 (500-¾)	1880-1¼ 457 (500-1¼)	1880-1½ 457 (500-1½)
CIRCLING	1920-1	495 (500-1)	1940-1½ 515 (600-1½)	2000-2 575 (600-2)

ALEXANDRIA, MINNESOTA
Amdt 1A 20MAY21

45°52'N-95°24'W

CHANDLER FLD (A.X.N)

RNAV (GPS) RWY 31

NC-1, 16 MAY 2024 to 13 JUN 2024

NC-1, 16 MAY 2024 to 13 JUN 2024