

WAAS
CH **40027**
W28D

APP CRS
281°

Rwy Idg
TDZE
Apt Elev

10102
1174
1203

RNAV (GPS) Y RWY 28R
PITTSBURGH INTL (PIT')

RNP APCH - GPS.

⚠

⚠

Circling Rwy 14 NA at night. Simultaneous approach authorized. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. For inop ALS, increase LNAV Cats C/D visibility to 1½ SM. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations.

MALSR

Ⓜ

Ⓜ

Ⓜ

Ⓜ

MISSED APPROACH: Climb to 1800 then climbing right turn to 4000 direct EWC VOR/DME and hold.

D-ATIS ARR 127.25 DEP 135.9	PITTSBURGH APP CON 123.95 360.8	PITTSBURGH TOWER 128.3 291.7	GND CON SOUTH 121.9 348.6 NORTH 127.8 348.6	CLNC DEL 126.75 353.7
---	---	--	---	---------------------------------

MISSED APCH FIX

6 NM

182°

1002°

ELLWOOD CITY EWC

CPDLC

(IAF) GRACE

4000 202° (22.4)

MSA RW28R 25 NM

3100

Ⓜ

1357

Ⓜ

1513±

1517

RW28R

(FAF) ZAIKO

3000 281° (9.3)

2041

2049

2049

(IF) NASTY

5000 321° (6.5)

(IAF) DIYAC

ELEV 1203

D

TDZE 1174

1800

4000

EWC

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).

281°

1800

4000

EWC

1.2 NM to RW28R

RW28R

ZAIKO 3000

NASTY 4000

3000

GP 3.00° TCH 55

1.2

4.3 NM

9.3 NM

REIL Rwy 10C

HIRL all Rwys

TDZ/CL Rwys 10L, 10R, 28L, 28R, 28C, and 32

CATEGORY	A	B	C	D
LPV DA	1374/18 200 (200-½)			
LNAV/VNAV DA	1629/45 455 (500-¾)			
LNAV MDA	1640/24 466 (500-½)		1640/50 466 (500-1)	
Ⓜ CIRCLING	1700-1 497 (500-1)		1880-2 677 (700-2)	1880-2¼ 677 (700-2¼)

PITTSBURGH, PENNSYLVANIA

Amdt 6 10AUG23

PITTSBURGH INTL (PIT')

40°29'N-80°14'W

RNAV (GPS) Y RWY 28R