

APP CRS	Rwy Idg	6500
349°	TDZE	96
	Apt Elev	153

RNAV (RNP) Z RWY 35

LIHUE (LIH)(PHLI)

GPS required. For inoperative MALSR, increase RNP 0.30 visibility to 1¾. For uncompensated Baro-VNAV systems, procedure NA below 14°C (57°F) or above 48°C (119°F).

MALSR

MISSED APPROACH: Climbing right turn to 3000 direct KREEN and hold.

ATIS 127.2	HCF CENTER 126.5 269.4	LIHUE TOWER ★ 118.9(CTAF) 263.1	GND CON 121.9
---------------	---------------------------	------------------------------------	------------------

ELEV 153 D TDZE 96

HIRL Rwy 17-35
REIL Rwys 3, 17 and 21
MIRL Rwy 3-21

TWR 198

6500 X 150

349°

35

A5

3000 KREEN

Procedure Turn NA

AKULE

MORKE

1900

349°

3000

GS 3.00° TCH 55

RW35

5.4 NM

5 NM

CATEGORY	A	B	C	D
RNP 0.30 DA	599-1¼ 503 (500-1¼)			

AUTHORIZATION REQUIRED

LIHUE, HAWAII

Orig-A 20OCT11

21°59'N-159°20'W

LIHUE (LIH)(PHLI)

RNAV (RNP) Z RWY 35