

WAAS
CH **45805**
W35B

APP CRS
356°

Rwy Idg **13400**
TDZE **564**
Apt Elev **607**

RNAV (GPS) RWY 35L

DALLAS-FORT WORTH INTL (DFW)

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C (25°F) or above 54°C (130°F). Simultaneous approach authorized with Rwy 36L/R and Rwy 35R. DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MALSR

MISSED APPROACH:

Climb to 3000 direct BBAKR and on track 357° to BOSSI and hold.

D-ATIS	REGIONAL APP CON	DFW TOWER	GND CON	CLNC DEL	CPDLC
ARR 123.775 DEP 135.925	127.075	126.55 127.5 EAST 124.15 134.9 WEST	121.65 121.8 EAST 121.85 WEST	128.25	

RADAR REQUIRED

MISSED APCH FIX

MSA RW35L 25 NM

TANDE

CORMN

DALLN

BEGGO

BBAKR

BOSSI

6000

5000

3000

2300

1897

GP 3.00°

TCH 47

3.2 NM

6.3 NM

2.4 NM

4.1 NM

1.2

*LNAV only.

*1.2 NM to RW35L

ELEV 607

TDZE 564

DALLAS-FORT WORTH, TEXAS

Amcl 2B 17AUG17

32°54'N-97°02'W

RNAV (GPS) RWY 35L