

LOC I-TVRRWY Idg5002

109.7

APP CRSTDZE86

357°

Apt Elev86

ILS or LOC RWY 36

VICKSBURG TALLULAH RGNL (TVR)

RNP APCH - GPS required for procedure entry at BARNE.

ADF required.

For inop ALS when using Vicksburg Muni, MS altimeter setting, increase S-LOC Cats C and D visibility to 1 3/8 SM. When local altimeter setting not received, use Vicksburg Muni, MS altimeter setting: increase S-ILS 36 DA to 309 feet; increase all MDAs 40 feet and visibility S-LOC 36 Cats C/D 1/8 SM and Circling Cats C/D 1/4 SM.

SSALR

MISSED APPROACH: Climb to 1200 then climbing left turn to 2100 direct TKH NDB and hold.

ASOS118.525	MEMPHIS CENTER132.5 259.1	UNICOM123.0 (CTAF)
-------------	---------------------------	--------------------

ELEV 86	D	TDZE 86
---------	---	---------

Knots	60	90	120	150	180
Min:Sec	6:00	4:00	3:00	2:24	2:00

1200	2100	TKH	TKH NDB 2061	One Minute Holding Pattern
			177°	4500
			357°	2100
			2100	GS 3.00° TCH 49'
		6 NM		
CATEGORY	A	B	C	D
S-ILS 36	286-1/2 200 (200-1/2)			
S-LOC 36	540-1/2	454 (500-1/2)	540-7/8	454 (500-7/8)
CIRCLING	540-1	454 (500-1)	720-1 3/4 634 (700-1 3/4)	720-2 634 (700-2)

TALLULAH, LOUISIANA

Amdt 1 05OCT23

32°21'N-91°02'W

VICKSBURG TALLULAH RGNL (TVR)

ILS or LOC RWY 36