


LOC/DME I-GXZ 110.1 Chan 38	APP CRS 275°	Rwy Idg TDZE Apt Elev	26R 8500 990 1026	26L 9999 996 1026
---	------------------------	-----------------------------	---	---

ILS or LOC RWY 26R

HARTSFIELD/JACKSON ATLANTA INTL (ATL)


RADAR required.

Simultaneous approach authorized.
For inop ALS, increase sidestep Rwy 26L Cats A and B visibility ¼ SM.





MISSED APPROACH: Climb to 1800 then climbing right turn to 4000 on RMG VORTAC R-132 to DALAS INT/RMG 18.5 DME and hold.

D-ATIS ARR 119.65	ATLANTA APP CON DEP 127.9 379.9	ATLANTA TOWER 8L-26R 8R-26L 9L-27R 9R-27L 10-28 RWYS				ALL RWYS (8L-26R,8R-26L) (9L-27R,9R-27L) 10-28 RWYS	GND CON DEP 121.75	ALL RWYS DEP 121.65 254.4
-----------------------------	--	---	--	--	--	---	------------------------------	--



ELEV 1026	TDZE 26R 990
	TDZE 26L 996



FAF to MAP 5.2 NM	Category	A	B	C	D
Knots	S-ILS 26R	1420/24	430 (400-½)	1420/40	430 (400-¾)
Min:Sec	S-LOC 26R	1420/55	424 (400-1)	1420-1¼	1420-1¾
	SIDESTEP 26L	1420/55	424 (400-1)	424 (400-1¼)	424 (400-1¾)

SE-4, 31 OCT 2024 to 28 NOV 2024

SE-4, 31 OCT 2024 to 28 NOV 2024