

APP CRS	Rwy Idg	<b>9001</b>
<b>154°</b>	TDZE	<b>43</b>
	Apt Elev	<b>46</b>

# RNAV (RNP) Z RWY 15




CHARLESTON AFB/INTL (CHS)

**⚠** For uncompensated Baro-VNAV systems, procedure NA below -5°C (23°F) or above 54°C (130°F). GPS required. For inop ALSF, increase RNP 0.11 all Cats visibility to RVR 4500 and RNP 0.30 all Cats visibility to RVR 6000.




**MISSED APPROACH:** Climb to 3000 on track 154° to SHRMP and hold.


D-ATIS	CHARLESTON APP CON	CHARLESTON TOWER	GND CON	CLNC DEL	CPDLC
<b>124.75</b>	<b>120.7 306.925</b>	<b>126.0 239.0</b>	<b>121.9 348.6</b>	<b>127.325 291.65</b>	



ELEV	<b>46</b>	TDZE	<b>43</b>
------	-----------	------	-----------



TDZ/CL Rwy 15  
REIL Rwy 3 and 21  
HIRL Rwy 3-21 and 15-33



GP 3.00°				
TCH 50				
CATEGORY	A	B	C	D
RNP 0.11 DA		315/24	272 (300-½)	
RNP 0.30 DA		428/45	385 (400-¾)	

## AUTHORIZATION REQUIRED