TEXOMA FIVE DEPARTURE

REGIONAL DEP CON
118.1 306.95 (NORTH)
135.975 379.9 (SOUTH)
ATIS
120.7
CLNC DEL
124.65
GND CON
121.9
MEACHAM TOWER
118.3 257.8

TOP ALTITUDE: ASSIGNED BY ATC

RADAR and DME required.

TULSA
114.4 TUL
Chan 91

WILL ROGERS
114.1 IRW
Chan 88

OKMULGEE
114.9 OKM
Chan 96

ARDMORE
116.7 ADM
Chan 114

BONHAM
114.6 BYP
Chan 93

RANGER
115.7 FUZ
Chan 104

ROLLS
DECKK
NOOGY
MRMAC
ZEMMA
EAKER
LOWGN
BLECO
GRABE

R-277
R-144
R-145
R-212
R-346
R-201
R-196
R-071
R-179
R-256

15000 *4500 303° (85)
4400 *2900 324° (30)
13000 *3000 021° (124)
11000 *3400 016° (90)
10000 *2700 360° (3)
15000 *2900 303° (60)
11000 *2900 325° (66)
9000 *2900 360° (56)
11000 *3700 012° (55)
4000 *2600 359° (46)
4000 *2200 348° (34)
4000 *2700 360° (34)
4000 *3200 012° (35)

MSA FUZ 25 NM
2700
3600
050°
310°

166°
149°
1600

TAKEOFF MINIMUMS
Rwys 16, 17: Standard.
Rwy 34: 300-1⅞ or standard with minimum climb of 225′/NM to 1100, or alternatively, with standard takeoff minimums and a normal 200′/NM climb gradient, takeoff must occur no later than 2000′ prior to DER.
Rwy 35: 300-1¼ or standard with minimum climb of 210′/NM to 900, or alternatively, with standard takeoff minimums and a normal 200′/NM climb gradient, takeoff must occur no later than 1300′ prior to DER.

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

SC-2, 03 OCT 2024 to 31 OCT 2024