RNAV (GPS) Y RWY 2L

NASHVILLE INTL (BNA)

WAAS	APP CRS	Rwy Idg	7702
CH 42713	021°	TDZE	599
W02A		Apt Elev	599

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C (13°F) or above 54°C (130°F). Use of FD or AP providing RNAV track guidance required during simultaneous operations. LNAV procedure NA during simultaneous operations. Simultaneous approach authorized with Rwy 2R. DME/DME RNP-0.3 NA.

ALSF-2

MISSED APPROACH: Climb to 4000 direct HIKRY and hold, continue climb-in-hold to 4000.

D-ATIS	NASHVILLE APP CON	NASHVILLE TOWER	GND CON	CLNC DEL	CPDLC
135.1	118.4 360.7	118.6 257.8	121.9 348.6	126.05	







CATEGORY	A	B	C	D
LPV DA	799/18 200 (200-½)			
LNAV/VNAV DA	949/30 350 (400-⅝)			
LNAV MDA	1020/24 421 (500-½)		1020/40 421 (500-¾)	
C CIRCLING	1100-1 501 (600-1)	1120-1 521 (600-1)	1200-1¾ 601 (700-1¾)	1380-2½ 781 (800-2½)

SE-1, 08 AUG 2024 to 05 SEP 2024
SE-1, 08 AUG 2024 to 05 SEP 2024