

LOC/DME I-EXR  
**110.9**  
Chan **46**

APP CRS  
**176°**

Rwy Idg **9802**  
TDZE **1287**  
Apt Elev **1296**

ILS or LOC RWY 17L  
WILL ROGERS WORLD (OKC)

DME required. RADAR required for procedure entry.

Simultaneous approach authorized. Inop table does not apply to S-ILS 17L. For inop ALS, increase S-LOC 17L visibilities Cats A and B to RVR 5500, and Cat E to 1 3/8 SM. RURIQ Fix Minimums: For inop ALS, increase S-LOC 17L visibilities Cats A and B to RVR 5500, and Cats C, D, and E to RVR 6000. Autopilot coupled approach NA below 1480.

MALSR  
AS

MISSED APPROACH: Climb to 5000 on heading 180° and on IRW VORTAC R-168 to JAVXE/IRW 11.6 DME and hold, continue climb-in-hold to 5000.

|                         |                                        |                                      |                               |                           |
|-------------------------|----------------------------------------|--------------------------------------|-------------------------------|---------------------------|
| D-ATIS<br><b>125.85</b> | OKE CITY APP CON<br><b>124.6 266.8</b> | ROGERS TOWER<br><b>119.35 269.45</b> | GND CON<br><b>121.9 348.6</b> | CLNC DEL<br><b>124.35</b> |
|-------------------------|----------------------------------------|--------------------------------------|-------------------------------|---------------------------|

| CATEGORY           | A                     | B             | C               | D               | E            |
|--------------------|-----------------------|---------------|-----------------|-----------------|--------------|
| S-ILS 17L          | 1487/40 200 (200-3/4) |               |                 |                 |              |
| S-LOC 17L          | 1740-40               | 453 (500-3/4) | 1740/45         | 453 (500-3/4)   |              |
| CIRCLING           | 1740-1                | 1760-1        | 1960-1 3/4      | 2000-2 1/4      | 2240-3       |
|                    | 444 (500-1)           | 464 (500-1)   | 664 (700-1 3/4) | 704 (800-2 1/4) | 944 (1000-3) |
| RURIQ FIX MINIMUMS |                       |               |                 |                 |              |
| S-LOC 17L          | 1680/40 393 (400-3/4) |               |                 |                 |              |
| CIRCLING           | 1740-1                | 1760-1        | 1960-1 3/4      | 2000-2 1/4      | 2240-3       |
|                    | 444 (500-1)           | 464 (500-1)   | 664 (700-1 3/4) | 704 (800-2 1/4) | 944 (1000-3) |

OKLAHOMA CITY, OKLAHOMA

Amtd 3E 30NOV23

35°24'N-97°36'W

WILL ROGERS WORLD (OKC)

ILS or LOC RWY 17L