ILS or LOC RWY 12R

ST LOUIS LAMBERT INTL (STL)

LOC/DME I-LMR	APP CRS		12R	12L
109.7	123°	Rwy Idg	10553	8956
Chan 34		TDZE	540	541
		Apt Elev	618	618

T LOC only: Rwy 12R helicopter visibility reduction below ¾ SM NA. Inop table does not apply to sidestep Rwy 12L. For inop ALS, increase S-ILS 12R Cat E visibility to RVR 4000 and increase S-LOC 12R Cats A/B visibility to RVR 5500, Cats C/D/E visibility to RVR 6000. Simultaneous approach authorized with Rwy 11. Simultaneous approach authorized with Rwy 12L requires use of vertical guidance; maintain last assigned altitude until established on glideslope.

MALSR Rwy 12R (A5)

ALSF-2 Rwy 12L (A)

MISSED APPROACH: Climb to 5000 on STL VORTAC R-128 to FONTI INT/STL 22.4 DME and hold, continue climb-in-hold to 5000.

D-ATIS	ST. LOUIS APP CON	ST. LOUIS TOWER	GND CON	CLNC DEL	CPDLC
125.025 379.925	132.125 360.6	118.5 257.7	121.9 348.6 (Inbound) 121.65 377.175 (Outbound) 118.925 227.125 (Rwy 11/29)	119.5 363.1	





HIRL all Rwys
TDZ/CL Rwys 11, 12L, 12R, 29, and 30R



FAF to MAP 5.7 NM					
Knots	60	90	120	150	180
Min:Sec	5:42	3:48	2:51	2:17	1:54

CATEGORY	A	B	C	D	E
S-ILS 12R	740/18 200 (200-½)				
S-LOC 12R	960/40 420 (400-¾)				
SIDESTEP 12L	980-1 439 (400-1)		980-1½ 439 (400-1½)	980-2 439 (400-2)	

NC-3, 31 OCT 2024 to 28 NOV 2024
NC-3, 31 OCT 2024 to 28 NOV 2024