

APP CRS	Rwy Idg	9000
123°	TDZE	618
	Apt Elev	618

RNAV (RNP) Z RWY 11


ST LOUIS LAMBERT INTL (STL)

V For uncompensated Baro-VNAV systems, procedure NA below -16°C (4°F) or above 54°C (130°F). Simultaneous approach authorized with Rwy 12L/R, except for arrivals at RRRPP and HRBEE. Use of FD or AP providing RNAV track guidance required during simultaneous operations. GPS required. For inop ALS, increase RNP 0.30 all Cats visibility to ¾.


ALS-F-2

MISSED APPROACH: Climb to 1100 then climbing right turn to 3000 direct IMPER and hold.

D-ATIS	ST. LOUIS APP CON	ST. LOUIS TOWER	GND CON	CLNC DEL	CPDLC
125.025 379.925	132.125 360.6	132.475 239.275	121.9 348.6 (Inbound) 121.65 377.175 (Outbound) 118.925 227.125 (Rwy 11/29)	119.5 363.1	



ELEV 618	D	TDZE 618
Rwy 6-24 7603 X 150		
Rwy 11-29 9000 X 150		
Rwy 12L-30R 9013 X 150		
Rwy 12R-30L 11020 X 150		



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 67).

See Planview for multiple IF locations.

1100	3000	IMPER
↑	↷	△

CATEGORY	A	B	C	D
RNP 0.30 DA		875-½	257 (300-½)	

HIRL all Rwys
TDZ/CL Rwys 11, 12L, 12R, 29, and 30R

ST. LOUIS, MISSOURI
Orig-B 17AUG17

38°45'N-90°22'W

ST LOUIS LAMBERT INTL (STL) RNAV (RNP) Z RWY 11

NC-3, 13 JUN 2024 to 11 JUL 2024

NC-3, 13 JUN 2024 to 11 JUL 2024