



# DORMR THREE DEPARTURE (RNAV)

D-ATIS DEP 128.475  
 CLINC DEL 133.6  
 CPDLC  
 GND CON 121.7 269.4  
 TAMPA TOWER 119.5 269.4  
 TAMPA DEP CON 118.8 239.3



NOTE: Jets only.

RNAV 1 - GPS.  
 RADAR required.

**TOP ALTITUDE:  
 6000**

**DEPARTURE ROUTE DESCRIPTION**

**TAKEOFF RUNWAYS 1L/R:** Climb on heading 007° to 540, then on heading 003° or as assigned by ATC, for vectors to SYKES, thence. . . .

**TAKEOFF RUNWAY 10:** Climb on heading 097° to 540, then on heading 093° or as assigned by ATC, for vectors to SYKES, thence. . . .

**TAKEOFF RUNWAY 19L:** Climb on heading 187° to 540, then on heading 213° or as assigned by ATC, for vectors to SYKES, thence. . . .

**TAKEOFF RUNWAY 19R:** Climb on heading 187° to 540, then on heading 203° or as assigned by ATC, for vectors to SYKES, thence. . . .

**TAKEOFF RUNWAY 28:** Climb on heading 277° to 540, then on heading 273° or as assigned by ATC, for vectors to SYKES, thence. . . .

. . . on track 269° to DORMR, then on assigned transition. Maintain 6000, expect filed altitude within 10 minutes after departure.


**CIGAR TRANSITION (DORMR3.CIGAR)**  
**FROOT TRANSITION (DORMR3.FROOT)**

**TAKEOFF MINIMUMS**

Rwys 1L/R, 19R, 28: Standard.

Rwy 10: Standard with minimum climb of 243' per NM to 800.

Rwy 19L: 200-1/2 or standard with minimum climb of 220' per NM to 300.



NOTE: Chart not to scale.