

WAAS CH 63147 W28A	APP CRS 280°	Rwy Ldg TDZE 588 Apt Elev 592
--	------------------------	---

RNAV (GPS) RWY 28

NIAGARA FALLS INTL (IAG)

RNP APCH - GPS.

▼


▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C.
Rwy 28 helicopter visibility reduction below RVR 4000 not authorized.
Circling Rwy 6 NA at night.
Circling NA for Cat E southeast of Rwy 6-24.
Inop table does not apply to LPV all Cats.
For inop ALS, increase LNAV/VNAV visibility all Cats to RVR 4500, LNAV visibility all Cats to RVR 5500.

MALSRL

MISSED APPROACH:
Climb to 1040 then climbing right turn to 3600 direct ZUPUV and hold, continue climb-in-hold to 3600.

ATIS 120.8 269.4	BUFFALO APP CON 126.5 317.6	NIAGARA TOWER ★ 118.5 (CTAF) 0 349.0	GND CON 125.3 275.8	UNICOM 122.95
----------------------------	---------------------------------------	--	-------------------------------	-------------------------



ELEV **592** **D** TDZE **588**

1040 3600 ZUPUV

VGSI and RNAV glidepath not coincident (VGSI Angle 2.50/TCH 67).

4 NM Holding Pattern

APIWO

KIGUW 2.9 NM to RW28

2300

1560

2300

GP 3.00° TCH 55

1.2 NM

1.7 NM

2.3 NM

6.9 NM

CATEGORY	A	B	C	D	E
LPV DA			838/40	250 (300-¾)	
LNAV/VNAV DA			957/40	369 (400-¾)	
LNAV MDA			960/40	372 (400-¾)	
CIRCLING	1100-1	508 (600-1)	1280-2 688 (700-2)	1280-2¼ 688 (700-2¼)	1280-2½ 688 (700-2½)