

WAAS CH 69632 W17A	APP CRS 169°	Rwy Idg 4808 TDZE 39 Apt Elev 40
--	------------------------	---


RNAV (GPS) RWY 17

WALLOPS FLIGHT FACILITY (WAL)


V For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C (13°F) or above
A 54°C (130°F), DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA.
 When local altimeter setting not received, use Salisbury altimeter setting: increase LPV DA to 372 and all Cats visibility ½ mile, increase LNAV/VNAV DA to 437 and all Cats visibility ¼ mile, increase all MDA 60 feet and LNAV Cats C/D visibility ½ mile and Circling Cat C visibility ¼ mile. Baro-VNAV and VDP NA when using Salisbury altimeter setting.

MISSED APPROACH: Climb to 600 then climbing right turn to 2000 direct MAGGO and hold.

ASOS 119.175	PATUXENT APP CON ★ 127.95 314.0	WALLOPS TOWER ★ 126.5 (CTAF) 0 306.975 (CTAF) 0	GND CON 127.875 269.325	CLNC DEL 121.7
-----------------	------------------------------------	--	----------------------------	-------------------



ELEV 40	TDZE 39
---------	---------



REIL all Rwy's
HIRI Rwy's 4-22, 10-28 and 17-35

WALLOPS ISLAND, VIRGINIA
Amdt 1B 21JUL16

37°56'N-75°28'W

WALLOPS FLIGHT FACILITY (WAL)
RNAV (GPS) RWY 17

NE-3, 16 MAY 2024 to 13 JUN 2024

NE-3, 16 MAY 2024 to 13 JUN 2024

VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 63).

5 NM Holding Pattern

DOVAY

2000 ← 349°
169° →

GP 3.00°
TCH 55

1700

6 NM

3.8 NM

1.3 NM

RW17

*1.3 NM to RW17

*LNAV only.

CATEGORY	A	B	C	D
LPV DA	322-1		283 (300-1)	
LNAV/VNAV DA	387-1½		348 (400-1½)	
LNAV MDA	500-1	461 (500-1)	500-1¾	461 (500-1¾)
C CIRCLING	600-1	560 (600-1)	620-1½ 580 (600-1½)	860-2¾ 820 (900-2¾)