WAAS CH 56331 W04A	APP CRS 043°	Rwy ldg 8748 TDZE 37 Apt Elev 40

RNAV (GPS) RWY 4
WALLOPS FLIGHT FACILITY (WAL)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C (13°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Salisbury altimeter setting: increase LPV DA to 342 and all Cats visibility ¼ mile; increase LNAV/VNAV DA to 510 and all Cats visibility ¼ mile; increase all MDA 60 feet and LNAV Cats C/D and Circling Cat C visibility ¼ mile. Baro-VNAV and VDP NA when using Salisbury altimeter setting.

MISSED APPROACH: Climb to 600 then climbing left turn to 2000 direct MAGGO and hold.

ASOS	PATUXENT APP CON ★	WALLOPS TOWER ★	GND CON	CLNC DEL
119.175	127.95 314.0	126.5 (CTAF) L 306.975 (CTAF) L	127.875 269.325	121.7





CATEGORY	A	B	C	D
LPV DA	287-¾ 250 (300-¾)			
LNAV/VNAV DA	455-1⅜ 418 (500-1⅜)			
LNAV MDA	560-1 523 (600-1)		560-1½ 523 (600-1½)	
C CIRCLING	600-1 560 (600-1)		620-1½ 580 (600-1½)	860-2¾ 820 (900-2¾)

REIL all Rwys
HIRL Rwys 4-22, 10-28 and 17-35

NE-3, 16 MAY 2024 to 13 JUN 2024