



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 5: Climb on heading 053° to 1100, then as assigned by ATC, thence....  
TAKEOFF RUNWAYS 14, 23, 32: Climb on heading as assigned by ATC, thence....  
....expect RADAR vectors to assigned route/navaid/fix. Maintain 2000.  
Expect filed altitude/flight level 10 minutes after departure.

TAKEOFF MINIMUMS:

Rwy 5: 300-1½ or standard with minimum climb of 435’ per NM to 500.  
Rwy 14: 300-1 or standard with minimum climb of 625’ per NM to 600.  
Rwy 23: 300-1 or standard with minimum climb of 350’ per NM to 400.  
Rwy 32: Standard.

- NOTE: Non RNAV equipped aircraft can expect vectors on assigned route.  
NOTE: BLZZR DEPARTURES expect vectors on BOS R-273.  
NOTE: BRUWN DEPARTURES expect vectors on BOS R-159.  
NOTE: CELTK DEPARTURES expect vectors on BOS R-114.  
NOTE: HYLND DEPARTURES expect vectors on BOS R-350.  
NOTE: PATSS DEPARTURES expect vectors on BOS R-260.  
NOTE: REVSS DEPARTURES expect vectors on BOS R-285.  
NOTE: SSOXS DEPARTURES expect vectors on BOS R-177.