

|  |                        |                             |                                      |
|--|------------------------|-----------------------------|--------------------------------------|
| WAAS<br>CH <b>61002</b><br><b>W28A</b> | APP CRS<br><b>276°</b> | Rwy Idg<br>TDZE<br>Apt Elev | <b>8394</b><br><b>7</b><br><b>65</b> |
|--|------------------------|-----------------------------|--------------------------------------|

# RNAV (GPS) Y RWY 28R

FORT LAUDERDALE/HOLLYWOOD INTL (FLL)


RNP APCH - GPS.

**⚠** Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. Inop table does not apply to LPV all Cats. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 7°C or above 54°C. For inop ALS, increase LNAV Cats C and D visibility to 1½ SM.





**MISSED APPROACH:**  
Climb to 800 then climbing right turn to 4000 direct HUKUK and hold, continue climb-in-hold to 4000.

|                        |                                       |  |                         |                          |       |
|------------------------|---------------------------------------|--|-------------------------|--------------------------|-------|
| D-ATIS<br><b>135.0</b> | MIAMI APP CON<br><b>133.775 285.6</b> | <b>FORT LAUDERDALE TOWER</b><br><b>119.3 257.8</b> | GND CON<br><b>121.4</b> | CLNC DEL<br><b>128.4</b> | CPDLC |
|------------------------|---------------------------------------|--|-------------------------|--------------------------|-------|



|         |          |        |
|---------|----------|--------|
| ELEV 65 | <b>D</b> | TDZE 7 |
|---------|----------|--------|



| CATEGORY          | A      | B           | C                      | D                      |
|-------------------|--------|-------------|------------------------|------------------------|
| LPV DA            |        | 257/40      | 250 (200-¾)            |                        |
| LNAV/VNAV DA      |        | 529/55      | 522 (500-1)            |                        |
| LNAV MDA          | 620/24 | 613 (600-½) | 620-1¾<br>613 (600-1¾) |                        |
| <b>C</b> CIRCLING | 680-1  | 615 (700-1) | 800-2<br>735 (800-2)   | 800-2¼<br>735 (800-2¼) |

SE-3, 30 DEC 2021 to 27 JAN 2022

SE-3, 30 DEC 2021 to 27 JAN 2022