

|                                        |                        |                                                     |
|----------------------------------------|------------------------|-----------------------------------------------------|
| WAAS<br>CH <b>61015</b><br><b>W06A</b> | APP CRS<br><b>063°</b> | Rwy Idg<br>TDZE <b>1107</b><br>Apt Elev <b>1156</b> |
|----------------------------------------|------------------------|-----------------------------------------------------|

RNAV (GPS) RWY 6

FORT DODGE RGNL (FOD)

RNP APCH.

Baro-VNAV NA when using Webster City altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. VDP NA when using Webster City altimeter setting. When local altimeter setting not received, use Webster City altimeter setting: increase LPV DA to 1349 feet; increase LNAV/VNAV DA to 1567 feet and all Cats visibility ¼ SM; increase all MDAs 60 feet and LNAV Cats C/D and Circling Cat C visibility ¼ SM. For inoperative MALSR when using Webster City altimeter setting, increase LPV all Cats visibility to 1 mile.

MALSR

MISSED APPROACH:  
Climb to 3000 direct  
OXDAH and hold.

|                            |                                          |                                        |
|----------------------------|------------------------------------------|----------------------------------------|
| AWOS-3PT<br><b>118.775</b> | MINNEAPOLIS CENTER<br><b>134.0 288.3</b> | UNICOM<br><b>123.0 (CTAF)</b> <b>📶</b> |
|----------------------------|------------------------------------------|----------------------------------------|

ELEV 1156 **D** TDZE 1107

4 NM Holding Pattern

3000 ← 243°  
063° →

GP 3.00°  
TCH 54

GEGQI

EYROV

RW06

OXDAH

6 NM

4 NM

1.2 NM

\*1.2 NM to RW06

\*LNAV only.

1254

6547 X 150

3301 X 100

0.6% UP

0.6% UP

063° to RW06

|              |                    |                    |                      |                     |
|--------------|--------------------|--------------------|----------------------|---------------------|
| CATEGORY     | A                  | B                  | C                    | D                   |
| LPV DA       | 1307-½ 200 (200-½) |                    |                      |                     |
| LNAV/VNAV DA | 1525-1 418 (400-1) |                    |                      |                     |
| LNAV MDA     | 1500-½ 393 (400-½) |                    |                      | 1500-1 393 (400-1)  |
| CIRCLING     | 1560-1 404 (500-1) | 1620-1 464 (500-1) | 1740-1½ 584 (600-1½) | 2080-3 924 (1000-3) |

MIRL Rwy 12-30 **📶**

HIRL Rwy 6-24 **📶**

REIL Rwy 12, 24 and 30 **📶**

FORT DODGE, IOWA  
Amdt 1B 20MAY21

42°33'N-94°12'W

FORT DODGE RGNL (FOD)  
RNAV (GPS) RWY 6