

VORTAC SZW <b>117.5</b> Chan <b>122</b>	APP CRS <b>173°</b>	Rwy Idg <b>7000</b> TDZE <b>83</b> Apt Elev <b>83</b>
---	------------------------	---


# VOR RWY 18

TALLAHASSEE INTL (TLH)

**ASR** Helicopter visibility reduction below 3/4 SM NA.  
VDP NA with Bainbridge altimeter setting.



MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 direct SZW VORTAC and hold.

ATIS <b>119.45 239.25</b>	TALLAHASSEE APP CON * <b>135.8 317.4</b>	TALLAHASSEE TOWER * <b>118.7 (CTAF) 0 257.8</b>	GND CON <b>121.9 348.6</b>	CLNC DEL <b>126.65 275.8</b>	UNICOM <b>123.075</b>
------------------------------	---	--	-------------------------------	---------------------------------	--------------------------



SE-3, 03 OCT 2024 to 31 OCT 2024

SE-3, 03 OCT 2024 to 31 OCT 2024



CATEGORY	A	B	C	D
S-18	780-1	697 (700-1)	780-2	697 (700-2)
<b>C</b> CIRCLING	780-1	697 (700-1)	780-2	800-2 1/4
			697 (700-2)	717 (800-2 1/4)
WAPIM FIX MINIMUMS				
S-18	540-1	457 (500-1)	540-1 3/8	457 (500-1 3/8)
<b>C</b> CIRCLING	580-1	600-1	640-1 1/2	800-2 1/4
	497 (500-1)	517 (600-1)	557 (600-1 1/2)	717 (800-2 1/4)