


WAAS CH 86310 W12A	APP CRS 121°	Rwy Idg 10501 TDZE 310 Apt Elev 312
--	------------------------	--

RNAV (GPS) RWY 12

WASHINGTON DULLES INTL (IAD)

RNP APCH.		MALSR	MISSED APPROACH: Climb to 4000 direct OTSUE and via 199° track to ZULKA and right turn via 298° track to OLIVR and hold.
<p>▼ For inop ALS, increase LNAV Cats C/D visibility to RVR 6000.</p> <p>▲ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 48°C.</p>			
D-ATIS 134.85	POTOMAC APP CON 120.45 306.925 (241°-330°) 128.525 306.925 (091°-240°) 126.1 338.25 (331°-090°)	DULLES TOWER 120.1 317.8 (Rwy 1R/19L) 120.25 348.6 (Rwy 1C/19C) 134.425 348.6 (Rwys 1L/19R and 12/30)	GND CON 121.9 317.8 (EAST) 121.625 348.6 (WEST)



NE-3, 31 OCT 2024 to 28 NOV 2024

NE-3, 31 OCT 2024 to 28 NOV 2024

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 66).				
KNUCK	↑ 4000	OTSUE	ZULKA	OLIVR
Procedure Turn NA		tr 199°	tr 298°	△
GP 3.00° TCH 49				
* INAV only.				
4500	1700	1180	1180	1180
10.9 NM	1.6 NM	1.5 NM	1.1 NM	
CATEGORY	A	B	C	D
LPV DA		510/18	200 (200-½)	
LNAV/VNAV DA		737/50	427 (500-1)	
LNAV MDA	720/24	410 (500-½)	720/40	410 (500-¾)
CIRCLING	940-1	628 (700-1)	940-1¾ 628 (700-1¾)	1180-2¾ 868 (900-2¾)

