

WAAS CH 65722 W31A	APP CRS 310°	Rwy Idg TDZE 1345 Apt Elev 1354
--	------------------------	---

RNAV (GPS) RWY 31
RANGE RGNL (HIB)

RNP APCH - GPS.



⚠ Baro-VNAV and VDP NA when using Eveleth altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Eveleth altimeter setting and increase LPV DA to 1581 feet; increase LNAV/VNAV DA to 1643 feet; increase all MDAs 40 feet; and Circling visibility Cat C ¼ SM. For inop ALS, increase LNAV/VNAV all Cats visibility to ⅜ SM, LNAV Cat C/D to 1 SM. For inop ALS when using Eveleth altimeter setting, increase LNAV/VNAV all Cats visibility to ⅝ SM.

MALS

A5

MISSED APPROACH: Climb to 3500 direct FENOK and hold.

ASOS 126.425	DULUTH APP CON 125.45 233.7	CLNC DEL 127.4	UNICOM 123.0 (CTAF) 0
------------------------	---------------------------------------	--------------------------	---------------------------------



3500	FENOK	VGSI and RNAV glidepath not coincident (VGSI Angle 2.90/TCH 62).	CEKSA	6 NM Holding Pattern
1860	HIBDA 1.5 NM to RW31	AYADO 3300	CEKSA 130° 12000 3500	GP 3.00° TCH 55
1 NM	0.5	4.5 NM	7 NM	
CATEGORY	A	B	C	D
LPV DA	1545-½ 200 (200-½)			
LNAV/VNAV DA	1607-½ 262 (300-½)			
LNAV MDA	1700-½ 355 (400-½)		1700-⅝ 355 (400-⅝)	
CIRCLING	1900-1 546 (600-1)		1920-1½ 566 (600-1½) 1980-2 626 (700-2)	

NC-1, 18 APR 2024 to 16 MAY 2024

NC-1, 18 APR 2024 to 16 MAY 2024