RNAV (GPS) RWY 27

ANOKA COUNTY/BLAINE (JANES FLD) (ANE)

WAAS CH 78300 W27A	APP CRS 269°	Rwy Idg 5000 TDZE 910 Apt Elev 912

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Crystal altimeter setting: increase LPV DA to 1131 feet; increase LNAV/VNAV DA to 1361 feet and all visibilities ⅛ SM, increase all MDA 40 feet and visibility Cat C/D ¼ SM, and Circling visibility Cat D ¼ SM. Baro-VNAV and VDP NA when using Crystal altimeter setting. For inop ALS when using Crystal altimeter setting, increase LNAV Cat C/D visibility to 1⅜ SM.

MALSR

MISSED APPROACH: Climb to 2700 direct GEP VORTAC and hold, continue climb-in-hold to 2700.

ATIS	MINNEAPOLIS APP CON	ANOKA TOWER★	GND CON	CLNC DEL	CLNC DEL	UNICOM
120.625	126.5 335.65	132.4 (CTAF) L	121.85	121.3	121.85 (When twr closed)	122.95

MISSED APCH FIX

GOPHER GEP

085°

265°

4 NM

MSA RW 27 25 NM

3500

1530

KOGGE 2.6 NM to RW27 (FAF) BOKYA

RW27

1065

1082

1426

2600

269°

(10.5)

HOLD 6000 3100

089°

4 NM

269°

3100 NoPT (IAF) STILS

271°

(8)

(IF/IAF) JUDAL

Procedure NA for arrivals at STILS on V78 eastbound.

2438

ELEV 912 TDZE 910

8

4855 X 100

5000 X 100

6

TWR

27

269°

36

964

HIRL Rwy 9-27 L

MIRL Rwy 18-36 L

REIL Rwys 9, 18, and 36 L

2700 GEP

JUDAL

4 NM Holding Pattern

KOGGE 2.6 NM to RW27

BOKYA

2600

089° 6000

269° 3100

1.2 NM to RW27

269°

RW27

2600

1780

GP 3.00°

TCH 49

1.2 NM 1.4 NM 2.6 NM 10.5 NM

CATEGORY	A	B	C	D
LPV DA	1110-½ 200 (200-½)			
LNAV/VNAV DA	1340-¾ 430 (500-¾)			
LNAV MDA	1340-½ 430 (500-½)		1340-¾ 430 (500-¾)	
C CIRCLING	1400-1 488 (500-1)		1420-1½ 508 (600-1½)	1580-2 668 (700-2)

NC-1, 03 OCT 2024 to 31 OCT 2024
NC-1, 03 OCT 2024 to 31 OCT 2024