

ZAAPA FIVE DEPARTURE (RNAV)

EC-2, 18 APR 2024 to 16 MAY 2024

ATIS
125.25
CLNC DEL
339.8
121.9 (when tower closed)
GND CON
121.9 339.8
LAKEFRONT TOWER ★
124.3 (CTAF) 339.8
CLEVELAND DEP CON
125.35 346.325

TOP ALTITUDE:
ASSIGNED BY ATC

TAKEOFF MINIMUMS:
Rwys 6L/R, 24R: Standard with a minimum climb of 500' per NM to 1100.
Rwy 24L: 400-1³/₄ or standard with minimum climb of 757' per NM to 1000.

NOTE: RADAR required.
NOTE: RNAV 1.
NOTE: DME/DME/IRU or GPS required.
NOTE: PUIJDL TRANSITION: For aircraft at or below FL220 only or as assigned by ATC.

350°
1100
246°
246°
350°
1100

MOHUM
9000
259°
(15)
ZAAPA
14000
265°
(5A)
YELOE
1400
221°
(34)
SINKR
1400
227°
(16)
SNNOH
1400
233°
(84)
PUIJDL

ZAAPA FIVE DEPARTURE (RNAV)
(ZAAPA5.ZAAPA) 26MAR20

CLEVELAND, OHIO
BURKE LAKEFRONT (BKL)

EC-2, 18 APR 2024 to 16 MAY 2024

▼ DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 6L/R: Climb on heading 066° to 1100, then on heading 350° or as assigned by ATC, maintain 2000 (do not climb above 2000) for RADAR vectors to cross MOHUM at or above 9000, thence....
TAKEOFF RUNWAY 24L/R: Climb on heading 246° to 1100, then right turn heading 350° or as assigned by ATC, maintain 2000 (do not climb above 2000) for RADAR vectors to cross MOHUM at or above 9000, thence....
....on track 259° to cross ZAAPA at or below 14000, then on (transition). Maintain ATC assigned altitude, expect filed altitude ten minutes after departure.

PUIJDL TRANSITION (ZAAPA5.PUIJDL)
SINKR TRANSITION (ZAAPA5.SINKR)
SNNOH TRANSITION (ZAAPA5.SNNOH)

NOTE: Chart not to scale.