

HOUSTON, TEXAS

AL-5461 (FAA)

24081

WAAS CH 97599 W15A	APP CRS 149°	Rwy Idg 10000 TDZE 95 Apt Elev 96
--	------------------------	--

RNAV (GPS) RWY 15R
GEORGE BUSH INTCNL/HOUSTON (IAH)

RADAR required for procedure entry.
RNP APCH.


T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -3°C or above 54°C. For inop ALS, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV all Cats visibility to RVR 5500, and LNAV Cat C/D/E visibility to 1 3/8 SM.

MALSR




MISSED APPROACH: Climb to 2000
direct JINIP and left turn on track
079° to COSBI and hold.

D-ATIS 124.05	HOUSTON APP CON 120.05 379.1 EAST 124.35 316.15 WEST	HOUSTON TOWER 127.3 288.25	GND CON 121.7	CLNC DEL 128.1	CPDLC
-------------------------	--	--------------------------------------	-------------------------	--------------------------	-------



ELEV 96	D	TDZE 95
---------	----------	---------



TDZ/CL Rwy's 8R, 8L, 15R, 26R, 26L,
27 and 33L
HURL all Rwy's

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 71).

CATEGORY	A	B	C	D	E
LPV DA		295/18	200 (200-½)		
LNAV/VNAV DA		460/35	365 (400-¾)		
LNAV MDA	580/24	485 (500-½)		580/50	485 (500-1)

HOUSTON, TEXAS
Amdt 2C 30JAN20

GEORGE BUSH INTCNTL/HOUSTON (IAH)

29°59'N-95°20'W

RNAV (GPS) RWY 15R

SC-5, 18 APR 2024 to 16 MAY 2024

SC-5, 18 APR 2024 to 16 MAY 2024