

ILS or LOC RWY 32

LOC/DME I-DAA

108.9

Chan 26

APCH CRS

322°

Rwy Idg

4529

TDZE

68

Arprt Elev

74

AL-5504 [USA]

DAVISON AAF (KDAV)

ADF required.

MAISF

A4

MISSED APPROACH: Climb to 800, then climbing left turn to 1700 direct DAA NDB and hold; or when directed by ATC, climb to 800, then climbing left turn to 2000 hdg 190° within 10 NM, expect RADAR vectors.

ATIS

128.175

POTOMAC APP CON

118.95 319.1

TOWER

124.275 (CTAF) 0 229.4

GND CON

121.9 351.8

CLNC DEL

351.8

PAR

Visibility reduction by helicopters NA.

Inoperative table does not apply to S-32 CAT A and B.

• 476

† If local altimeter setting not received, use Ronald Reagan Washington National altimeter setting.

LOCALIZER 108.9

I-DAA

Chan 26

410

278

P-73

IAF

DAVEE

223

DAA

I-DAA 5.1

1700

039°

(22.6)

BROOKE

114.5 BRV

Chan 92

1700

008°

(7.8)

IRONS

800

1700

DAA

NDB

I-DAA 5.1

1492

142°

322°

1700

1500

GS 3.00°

TCH 34

4.3 NM

CATEGORY	A	B	C	D
S-ILS 32	348/50		280 (300-1)	
S-LOC 32*	540/50 472 (500-1)		540/60 472 (500-1¼)	
CIRCLING	740-1 666 (700-1)	740-1¾ 666 (700-1¾)		760-2¼ 686 (700-2¼)
† RONALD REAGAN WASHINGTON NATIONAL ALTIMETER SETTING MINIMUMS				
S-ILS 32	381/50 313 (400-1)			
S-LOC 32**	580/50 512 (600-1)		580-1½ 512 (600-1½)	
CIRCLING	780-1 706 (800-1)	780-2 706 (800-2)		800-2¼ 726 (800-2¼)

ELEV 74

TDZE 68

Rwy 14 Idg 4930'

Rwy 32 Idg 4529'

MSA DAA 25 NM

2100

HIRL Rwy 14-32

FAF to MAP 4.3 NM

Knots	60	90	120	150	180
Min:Sec	4:18	2:52	2:09	1:43	1:26

TWR 117

0.3% DOWN

A4

322°

NE-3, 18 APR 2024 to 16 MAY 2024

NE-3, 18 APR 2024 to 16 MAY 2024

FORT BELVOIR, VIRGINIA
Amdt 12C 16JUL20

38°43'N-77°11'W

DAVISON AAF (KDAV)

ILS or LOC RWY 32