

WAAS CH 62823 W21A	APP CRS 206°	Rwy Idg TDZE Apt Elev	5502 315 315
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 21

SIKESTON MEML MUNI (SIK)

RNP APCH.



▽


△NA

Rwy 21 helicopter visibility reduction below ¾ SM NA. Baro-VNAV NA when using Cape Girardeau altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Cape Girardeau altimeter setting and increase all DA 49 feet and all MDA 60 feet. Increase LNAV and Circling Cat C/D visibility ¼ SM.

MISSED APPROACH: Climb to 2000 direct CUXID and hold.

AWOS-3 119.175	MEMPHIS CENTER 133.65 292.15	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



2000 ↑	CUXID 				
*LNAV only					
RW21					
1.6		3.6 NM		6.8 NM	
CATEGORY	A	B	C	D	
LPV DA	565-1 250 (300-1)				
LNAV/VNAV DA	761-1½ 446 (500-1½)				
LNAV MDA	720-1 405 (500-1)		720-1½ 405 (500-1½)		
 CIRCLING	840-1 525 (600-1)	860-1 545 (600-1)	1080-2¼ 765 (800-2¼)	1160-2¾ 845 (900-2¾)	