


WAAS CH 42820 W08A	APP CRS 077°	Rwy Idg TDZE Apt Elev	7723 1274 1277
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 8
CENTRAL WISCONSIN (CWA)

RNP APCH - GPS.			MALSR 	MISSED APPROACH: Climb to 3000 direct ASARE and hold.	
  For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. For inop ALS, increase LNAV Cat C and D visibility to 1½ SM.					
ATIS 127.45	MINNEAPOLIS CENTER 124.4 317.7	CWA TOWER ★ 119.75 (CTAF)  360.7		GND CON 121.9 360.7	UNICOM 122.95



4 NM Holding Pattern TUCYU		HENPA 3000		3000 ASARE	
6000 ← 257° 3000 → 077°		077°		WOKOS 1.7 NM to RW08 1.1 NM to RW08	
GP 3.00° TCH 55		3000		1860	
7.6 NM		3.6 NM		0.6 NM 1.1 NM	
CATEGORY	A	B	C	D	
LPV DA	1474-½		200 (200-½)		
LNAV/VNAV DA	1601-½		327 (400-½)		
LNAV MDA	1640-½	366 (400-½)	1640-¾	366 (400-¾)	
CIRCLING	1740-1	463 (500-1)	1740-1½ 463 (500-1½)	1840-2 563 (600-2)	