

WAAS CH 65717 W20A	APP CRS 195°	Rwy Idg 5900 TDZE 984 Apt Elev 984
--	------------------------	---

RNAV (GPS) RWY 20
FAYETTEVILLE MUNI (FYM)



RNP APCH - GPS

NA For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 46°C (114°F). Rwy 20 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received use Huntsville Exec Tom Sharp Jr Fld altimeter setting and increase LPV DA to 1373 feet and all visibilities ½ SM; LNAV/VNAV DA to 1561 feet and all visibilities ¼ SM; increase all MDAs 120 feet and LNAV Cat C/D and Circling Cat C visibility ½ SM, Circling Cat D visibility ¼ SM. Baro-VNAV and VDP NA when using Huntsville Exec Tom Sharp Jr Fld altimeter setting. Inoperative table does not apply to LNAV/VNAV all Cats. Inoperative table does not apply to LNAV Cat C when using Huntsville Exec Tom Sharp Jr Fld altimeter setting.

ODALS

MISSED APPROACH:
Climb to 3000 direct EZBUV and hold.

AWOS-3 135.275	HUNTSVILLE APP CON ★ 125.6 354.1	CLNC DEL (GCO) 121.725	UNICOM 122.8 (CTAF) 0
--------------------------	--	----------------------------------	---------------------------------



3000	EZBUV	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 20).	NIVLE	4 NM	Holding Pattern
* LNAV only.					
* 1.2 NM to RW20					
ONDOW					
RW20					
GP 3.00° TCH 40					
1.2 NM 2.8 NM 6.2 NM					
CATEGORY	A	B	C	D	
LPV DA	1260-1 276 (300-1)				
LNAV/VNAV DA	1448-1¾ 464 (500-1¾)				
LNAV MDA	1380-¾ 396 (400-¾)				1380-1¼ 396 (400-1¼)
CIRCLING	1420-1 436 (500-1)	1540-1 556 (600-1)	1580-1½ 596 (600-1½)	1580-2 596 (600-2)	

SE-1, 16 MAY 2024 to 13 JUN 2024

SE-1, 16 MAY 2024 to 13 JUN 2024