




LOC I-DTO 109.1	APP CRS 177°	Rwy Idg 18L 18R TDZE 6502 5003 642 643 Apt Elev 643 643
---------------------------	------------------------	---

ILS or LOC RWY 18L

DENTON ENTERPRISE (D'TO)

ADF required. RADAR required for procedure entry.				MALSR AG	MISSED APPROACH: Climb to 2500 then right turn direct PINCK LOM and hold.
<p>▼ For inop ALS, increase S-ILS 18L all Cts visibility to ½ SM. For inop ALS, increase S-LOC 18L Cat C/D to 1½ SM.</p> <p>▲ NA</p>					
ATIS 119.325	REGIONAL APP CON 118.1 306.95	DENTON TOWER* 119.95 (CTAF)	GND CON 123.95	CLNC DEL 123.95	UNICOM 122.95



CATEGORY	A	B	C	D
S-ILS 18L		842-½	200 (200-½)	
S-LOC 18L	1160-½	518 (600-½)	1160-1	518 (600-1)
SIDESTEP 18R	1260-1	617 (700-1)	1260-1¾ 617 (700-1¾)	1260-2 617 (700-2)
CIRCLING	1260-1	617 (700-1)	1380-2 737 (800-2)	1380-2¼ 737 (800-2¼)