WAAS CH 72630 W11A	APP CRS 111°	Rwy ldg 5001 TDZE 1152 Apt Elev 1171

RNAV (GPS) RWY 11
IOWA COUNTY (MRJ)

Baro-VNAV NA when using Platteville altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). When local altimeter setting not received, use Platteville altimeter setting and increase all DA 55 feet, increase LPV and LNAV/VNAV all Cats visibility ⅛ mile, increase all MDA 60 feet, and LNAV Cat C visibility ¼ mile. DME/DME RNP-0.3 NA.

MISSED APPROACH: Climb to 3600 direct YECNU and hold.

AWOS-3	CHICAGO CENTER	UNICOM
118.525	133.95 281.4	122.8 (CTAF) L



ELEV 1171	TDZE 1152



CATEGORY	A	B	C	D
LPV DA	1352-¾ 200 (200-¾)			NA
LNAV/VNAV DA	1402-⅞ 250 (300-⅞)			NA
LNAV MDA	1520-1 368 (400-1)		1520-1⅛ 368 (400-1⅛)	NA
CIRCLING	1620-1 449 (500-1)	1640-1 469 (500-1)	1640-1½ 469 (500-1½)	NA

REIL Rwys 11 and 29 L
MIRL Rwys 4-22 and 11-29 L

EC-3, 18 APR 2024 to 16 MAY 2024
EC-3, 18 APR 2024 to 16 MAY 2024