

WAAS CH 72917 W07A	APP CRS 074°	Rwy Idg TDZE Apt Elev	7299 1460 1478
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 7R

PHOENIX DEER VALLEY (DVT)


RNP APCH - GPS.

▼

When VGSI inop, Circling Rwy 25R NA at night. When local altimeter setting not received, use Scottsdale altimeter setting: increase LPV DA to 1822 feet and all visibilities ½ SM, increase LNAV/VNAV DA to 2160 feet and all visibilities ½ SM, increase all MDAs 40 feet and increase Circling Cat B visibility ¼ SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Baro VNAV and VDP NA when using Scottsdale altimeter setting. Circling NA north of Rwy 7R-25L at night.

MISSED APPROACH: Climb to 5000 direct VIFPE and track 069° to AVENT and hold, continue climb-in-hold to 5000.

ATIS 126.5	PHOENIX APP CON 120.7 239.0	DEER VALLEY TOWER ★ 118.4 (070°-250°) (CTAF) 120.2 (251°-069°)	GND CON 121.8	CLNC DEL 123.9	UNICOM 122.95
----------------------	---------------------------------------	--	-------------------------	--------------------------	-------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 46).

5000

VIFPE

tr 069°

AVENT

BOLES

CEGAP

JURUX 3 NM to RW07R

1.8 NM to RW07R

RW07R

GP 3.00° TCH 42

3900

2900

2440

6 NM

1.4 NM

1.2 NM

1.8 NM

GP 3.00° TCH 42

0.5% UP

0.5% UP

81% X 100

0.4% DOWN

TWR 1637 ±

4500 X 75

25R

25L

CATEGORY	A	B	C	D
LPV DA		1795-1½	335 (400-1½)	
LNAV/VNAV DA		2133-2½	673 (700-2½)	
LNAV MDA	2060-1	600 (600-1)	2060-1¾	600 (600-1¾)
CIRCLING	2400-1¼ 922 (1000-1¼)	2420-1¼ 942 (1000-1¼)	2580-3 1102 (1200-3)	2700-3 1222 (1300-3)

MIRL Rwy 7L-25R and 7R-25L
REIL Rwy 7L, 7R, 25L, and 25R