18 APR 2024 to

16 MAY 2024

## WEAZL FIVE DEPARTURE (RNAV)

RNAV 1 - DME/DME/IRU or GPS. **TOP ALTITUDE:** CHARLOTTE DEP CON 128.325 307.8 3000 RADAR required. AWOS-3 128.175 CLNC DEL 121.75 254.375 **GND CON** 121.75 254.375 CLAWD **≺** STANLY COUNTY TOWER \* 126.275 291.9 1.430C \*6400 -003° (45) NOTE: For turbo jets only. NOTE: If unable to accept climb rates, advise ATC on initial contact. NOTE: Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable advise ATC. WEAZL ≺ SA VUJ 25 M 3100 WHFRD

## TAKEOFF MINIMUMS

Rwys 4L, 22R: NA-Environmental.

Rwy 22L: Standard.

Rwy 4R: 300-13/4 or standard with minimum climb of 315' per NM 1000.



NOTE: Chart not to scale



## DEPARTURE ROUTE DESCRIPTION

Climb on heading assigned by ATC, on RADAR vectors to WHFRD, then on track 003° to WEAZL. Then on CLAWD Transition. Maintain 3000, expect clearance to filed altitude within 10 minutes after departure.

CLAWD TRANSITION (WEAZL5.CLAWD)