ATIS 126.925
CLNC DEL 128.725
GND CON 132.65 306.2
ALLIANCE TOWER 135.15 257.9
REGIONAL DEP CON 118.1 306.95
TAKEOFF MINIMUMS
Rwys 16L/R: 300-2¼ or standard with minimum climb of 220' per NM to 1100, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 1900' prior to DER.
Rwys 34L/R: Standard.
TOP ALTITUDE: ASSIGNED BY ATC
1100
169°
SALVE
8500
*2100
090°
(8)
KUSSO
ZERLU
10000
*2100
025°
(11)
SWDIA
10000
*2100
064°
(27)
ZACHH
10000
*2100
064°
(86)
BSKAT
10000
*1900
057°
(40)
LOOSE
10000
*2400
067°
(62)
TRCH
10000
*2000
066°
(27)
JAYXX
10000
*2000
066°
(85)
TRYTN
10000
*2000
066°
(85)
HANUH
10000
*1900
109°
(6)
10000
*1900
144°
(10)
THHOR
10000
*2000
091°
(25)
JJANE
10000
*2600
092°
(54)
LYING
10000
*2000
080°
(25)
FORCK
10000
*2100
080°
(80)
MRSSH
10000
*2100
105°
(70)
ZALEA
115°
10000
*1900
(35)
BDDAY
N
NOTE: Chart not to scale.
NOTE: RADAR required.
NOTE: RNAV 1.
NOTE: DME/DME/IRU or GPS required.
NOTE: BDDAY Transition: ATC assigned only.
NOTE: MRSSH Transition: For aircraft inbound to Shreveport, Jackson and Monroe terminal area airports only
(NARRATIVE ON FOLLOWING PAGE)