

WAAS CH 58221 W35A	APP CRS 348°	Rwy Idg TDZE Apt Elev	6300 5022 5022
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 35


NEPHI MUNI (U14)

RNP APCH - GPS.

NA Baro-VNAV NA when using Provo altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -24°C or above 12°C. Circling NA for Cat C east of Rwy 17 and 35. Rwy 35 helicopter visibility reduction below ¾ SM NA. VDP NA with Provo altimeter setting. When local altimeter setting not received, use Provo altimeter setting: increase LPV DA to 5416 feet and visibility all Cats ½ SM, increase LNAV/VNAV DA to 5740 feet and visibility all Cats ½ SM; increase all MDAs 160 feet and LNAV visibility Cats B/C/D and Circling visibility Cats A/B ½ SM.

MISSED APPROACH: Climb to 8200 then climbing left turn to 10600 direct PILTE and hold.



AWOS-3 118.275	SALT LAKE CENTER 127.825 239.025	UNICOM 123.075 (CTAF) 0
--------------------------	--	-----------------------------------



SW-4, 03 OCT 2024 to 31 OCT 2024

SW-4, 03 OCT 2024 to 31 OCT 2024

ELEV 5022	TDZE 5022
-----------	-----------



CATEGORY	A	B	C	D
LPV DA		5272-7/8	250 (300-7/8)	
LNAV/VNAV DA		5596-2	574 (600-2)	
LNAV MDA	5940-1¼	918 (1000-1¼)	5940-2½	918 (1000-2½)
CIRCLING	5900-1¼	878 (900-1¼)	6920-3 1898 (1900-3)	NA