

TACAN RWY 3

TACAN COF
Chan 97

APCH CRS
020°

Rwy ldg
TDZE
Arpt Elev

9008
5
8

AL-38 [USAF]

PATRICK SFB (KCOF)

▼ * When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CDE vis to 1 3/8 miles.
** Circling not authorized NW of Rwy 3-21.

ALSF-1
(A1)

MISSED APPROACH: Climb to 600, then climbing right turn to 3000 and intercept COF TACAN R-110 to ZEVEX/12 DME and hold, continue climb in hold to 3000.

ATIS ★
119.175 273.5

ORLANDO APP CON
132.65 281.425

TOWER ★
133.75 269.375

GND CON
124.35 335.8

CLNC DEL
118.4 289.4

** When circling to Rwy 29 at night, operational VGSI required, remain on or above VGSI glidepath until threshold.

The main chart displays the TACAN RWY 3 approach. Key features include:

- Obstacles:** 1046 (left), 506 (top), 333, 475, 300, 43, 80, 116, 124, 124, 278, 525, 429, 166.
- Navigation Aids:** PATRICK Chan 97 COF, CUPKU COF 5, RADAR, MILME 7.1, (IF) CEVIM COF 12, (IAF) ZEVEX COF 12, MSA COF 2.5 NM.
- Approach Paths:** R-110 (110°/290°), COF 12 Arc 3000, R-200, LR-190.
- Altitudes:** 200, 8000, 3000, 124, 116, 124, 278, 525, 429, 166.
- Emergency:** EMERG SAFE ALT 100 NM 3000.

This inset chart shows the Rwy 29 ldg 3687' and the HIRL Rwy 3-21 and MIRL Rwy 11-29. It includes:

- Obstacles:** 152, 109, 12, 3992, 200, 208, 200, 166.
- Navigation Aids:** TWR, (A1).
- Approach Paths:** 020°.

The bottom chart shows the approach paths, altitudes, and navigation aids. Key features include:

- Obstacles:** 600, 3000, 3000, 2000, 1400, 2.4, 1.9, 3.16°, 3.5 NM, 0.5.
- Navigation Aids:** CEVIM 12, MILME 7.1, CUPKU 5, RADAR, TACAN, DOMGE.
- Approach Paths:** 020°, 3000, 2000, 1400, 3.16°, 3.5 NM, 0.5.
- Altitudes:** 3000, 2000, 1400, 2.4, 1.9, 3.16°, 3.5 NM, 0.5.

Cocoa Beach, Florida
Amdt 5 02NOV23

28° 14' N - 80° 37' W

PATRICK SFB (KCOF)

TACAN RWY 3