



WAAS CH 45999 W16A	APP CRS 164°	Rwy Idg TDZE 163 Apt Elev 171
--	------------------------	---

RNAV (GPS) Y RWY 16

BELLINGHAM INTL (BLI)

RNP APCH. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -10°C or above 54°C. #RVR 1800 authorized with use of FD or AP or HUD to DA.	MALSR 	MISSED APPROACH: Climb to 700 then climbing right turn to 2000 direct TECUV and hold.
---	---------------------------------	--

ATIS 134.45	VICTORIA TERMINAL APP CON 132.7 290.8	BELLINGHAM TOWER ★ 124.9 (CTAF) 0 379.3	GND CON 127.4 379.3	UNICOM 122.95
-----------------------	---	---	-------------------------------	-------------------------



4 NM Holding Pattern		SECOG	WUGUT	700	2000	TECUV
6000 ← 344°		2000 → 164°	2000			
GP 3.00°						
TCH 51						
		6 NM	4.5 NM	1.1 NM		
CATEGORY	A	B	C	D	*LNAV only	
LPV DA #	363/24		200 (200-½)			
LNAV/VNAV DA	491/30		328 (400-¾)			
LNAV MDA	560/24		560/35		397 (400-¾)	
C CIRCLING	640-1		900-2		1160-3	
	469 (500-1)		729 (800-2)		989 (1000-3)	