

WAAS CH 50518 W32A	APP CRS 319°	Rwy Idg 10000 TDZE 442 Apt Elev 459
--	------------------------	--

RNAV (GPS) RWY 32R

SCOTT AFB/MIDAMERICA ST LOUIS (BLV)

RNP APCH - GPS.

⚠


ASR

For uncompensated Baro-VNAV systems,
procedure NA below -18°C or above 54°C.
For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 5500.

MALSR

MISSED APPROACH: Climb to 2300 direct MADDT and right turn on track 078° to JIKMO and on track 145° to COFEY and hold.

ATIS ★ 128.7 256.7	ST LOUIS APP CON 125.2 281.5	SCOTT TOWER 128.25 253.5	GND CON 119.2 275.8	CLNC DEL 119.875 263.025
------------------------------	--	------------------------------------	-------------------------------	------------------------------------



ELEV 459

D

TDZE 442

↑

MADDT

↷ tr 078°

JIKMO

tr 145°

COFEY

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).

AFEBE 2200

OJAMO

ENRRN 3 NM to RWY 32R

1 NM to RWY 32R

RWY 32R

1460

2200

319°

GP 3.00° TCH 55

REIL Rwy 14L
HIRL Rwy 14R-32L and 14L-32R

CATEGORY	A	B	C	D
LPV DA	642/24 200 (200-½)			
LNAV/VNAV DA	804/35 362 (400-⅝)			
LNAV MDA	840/24 398 (400-½)		840/35 398 (400-⅝)	
CIRCLING	1000-1 541 (600-1)	1120-1 661 (700-1)	1240-2¼ 781 (800-2¼)	1240-2½ 781 (800-2½)