

CHARLOTTE/DOUGLAS INTL (CLT)
CHARLOTTE, NORTH CAROLINA

KWEEN FIVE DEPARTURE (RNAV)

TOP ALTITUDE:
8000

RNAV 1 - DME/DME/IRU or GPS.

RADAR required.

NOTE: For turbo jets only.

NOTE: Transponder code will be issued via PDC or Charlotte CLNC DEL.

NOTE: If unable to accept climb rates, advise ATC on initial contact.

NOTE: Accelerate to 250K, if unable advise ATC. Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable advise ATC.

A circular gauge face for an MSA CLT 25 NM. The text "MSA CLT 25 NM" is curved along the top inner edge. In the center, there is a rectangular display showing the number "3800". Below the display is a small circular symbol with a crosshair.

TAKEOFF MINIMUMS

Rwys 18L/C/R, 36C/R: Standard with minimum climb of 500' per NM to 1260.
Rwy 36L: Standard with minimum climb of 500' per NM to 1400.

FL180
*2300
135°
(75)

P|TRW

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

KWEEN FIVE DEPARTURE (RNAV)

(KWEEN5.KWEEN) 21MAR24

CHARLOTTE, NORTH CAROLINA
CHARLOTTE/DOUGLAS INTL (CLT)

SE-2, 16 MAY 2024 to 13 JUN 2024