


LOC/DME I-MED	APP CRS	Rwy Idg
111.1	093°	12246
Chan 48		TDZE 672
		Apt Elev 680

ILS or LOC RWY 10L

CHICAGO O'HARE INTL (ORD)

From GIBNS: RNAV-1 GPS required.				ALSIF-2 	MISSED APPROACH: Climb to 4000 on heading 093° and CGT VORTAC R-336 to CGT VORTAC and hold.	
RNAV 1-GPS or RADAR required for procedure entry. DME or RADAR required.						
Simultaneous approach authorized.						
D-ATIS 135.4 282.225	CHICAGO APP CON 119.0 292.125	O'HARE TOWER 132.7 348.0	GND CON 124.125 (TWR NORTH) 118.05 (TWR SOUTH) 226.675 (ALL TWRs)	(TWR CENTER) 121.75 (OBND) 121.9 (IBND)	CLNC DEL 121.6	CPDLC



ARIST I-MED [28.4] RADAR	KALZO I-MED [25.2] RADAR	BURKE I-MED [22.1] RADAR	PRATT I-MED [15.8] RADAR	SYSCO I-MED [18.9] RADAR	CARLE I-MED [12.7] RADAR	BUGSE INT I-MED [7.3] RADAR	POPME INT I-MED [3.9] RADAR	IM
9000	8000	7000	6000	5000	4000	2300	1200	
3.1 NM	3.1 NM	3.1 NM	3.1 NM	3.1 NM	5.4 NM	3.4 NM	1.4 NM	0.1 NM
*LOC only.								
POPME FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)								
S-ILS 10L	872/18		200 (200-½)					
S-LOC 10L	1200/24	528 (600-½)	1200/55	528 (600-1)				
S-LOC 10L	1080/24	408 (400-½)	1080/40	408 (400-¾)				

