

APP CRS 320°	Rwy Idg	7278
	TDZE	793
	Apt Elev	796

RNAV (RNP) Z RWY 32

INDIANAPOLIS INTL (IND)

▼

For uncompensated Baro-VNAV systems, procedure NA below -18°C (2°F) or above 54°C (130°F). GPS required.

MALSR

MISSED APPROACH: Climb to 3000 on track 320° to KEADY and hold.

D-ATIS 134.25	INDIANAPOLIS APP CON 128.175 317.8	INDY TOWER 120.9 257.8	GND CON 121.9	CLNC DEL 128.75 257.8	CPDLC
------------------	---------------------------------------	---------------------------	------------------	--------------------------	-------

The main chart displays the RNP Z RWY 32 procedure. Key features include:

- Initial Approach:** Starts at 1159, descends to 1546, then to 1400 (5.3) and 139°.
- Intermediate Approach:** Descends to 1252, then to 3600 (20.5) and 205°.
- Final Approach:** Descends to 2400 (4.6) and 320°, then to 2400 (4.6) and 320°.
- Obstacles:** HIKEK (3600, 07.5), EVAVE (200K), BDAWG (5000, RF REQD), and OZMOE (4500, 210K).
- Navigation Aids:** KEADY (3000), BTTLR (2400), and CUREG (200K).
- Altitudes:** 1159, 1546, 1400 (5.3), 139°, 1252, 3600 (20.5), 2400 (4.6), 320°, 2400 (4.6), 320°.
- Distance:** 4.9 NM.

The inset chart shows the HIRL all Rwy, TDZ/CL Rwy 5L and 5R, and a planview of the RWY 32 approach. Key features include:

- Altitudes:** 796, 793.
- Distance:** 4.9 NM.
- Navigation Aids:** KEADY (3000), BTTLR (2400), and CUREG (200K).
- Altitudes:** 1159, 1546, 1400 (5.3), 139°, 1252, 3600 (20.5), 2400 (4.6), 320°, 2400 (4.6), 320°.
- Distance:** 4.9 NM.

VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 73).				
BTTLR 2400				
GP 3.00° TCH 53				
See planview for multiple IF locations.				
4.9 NM				
CATEGORY	A	B	C	D
RNP 0.19 DA	1134/30 341 (400-%)			
RNP 0.30 DA	1196/45 403 (400-%)			
AUTHORIZATION REQUIRED				

INDIANAPOLIS, INDIANA

Amdt 2 10NOV16

39°43'N-86°18'W

INDIANAPOLIS INTL (IND)

RNAV (RNP) Z RWY 32