

|                                        |                        |                                                   |                                         |
|----------------------------------------|------------------------|---------------------------------------------------|-----------------------------------------|
| WAAS<br>CH <b>87029</b><br><b>W03A</b> | APP CRS<br><b>032°</b> | Rwy Idg<br>TDZE <b>860</b><br>Apt Elev <b>887</b> | <b>6769</b><br><b>860</b><br><b>887</b> |
|----------------------------------------|------------------------|---------------------------------------------------|-----------------------------------------|



RNAV (GPS) RWY 3

DANE COUNTY RGNL/TRUAX FLD (MSN)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA.

MISSED APPROACH: Climb to 3600 direct FONUV and hold.

|                             |                                          |                                                |                               |                            |                         |
|-----------------------------|------------------------------------------|------------------------------------------------|-------------------------------|----------------------------|-------------------------|
| ATIS<br><b>124.65 278.3</b> | MADISON APP CON ★<br><b>135.45 343.7</b> | MADISON TOWER ★<br><b>119.3 (CTAF) 0 257.8</b> | GND CON<br><b>121.9 348.6</b> | CLNC DEL<br><b>121.625</b> | UNICOM<br><b>122.95</b> |
|-----------------------------|------------------------------------------|------------------------------------------------|-------------------------------|----------------------------|-------------------------|



| CATEGORY     | A                     | B                     | C                       | D                       |
|--------------|-----------------------|-----------------------|-------------------------|-------------------------|
| LPV DA       |                       | 1060-¾                | 200 (200-¾)             |                         |
| LNAV/VNAV DA |                       | 1179-1                | 319 (300-1)             |                         |
| LNAV MDA     | 1320-1                | 460 (500-1)           | 1320-1¾                 | 460 (500-1¾)            |
| CIRCLING     | 1420-1<br>533 (600-1) | 1460-1<br>573 (600-1) | 1460-1½<br>573 (600-1½) | 1700-2¾<br>813 (900-2¾) |

