


WAAS CH 93607 W27A	APP CRS 273°	Rwy Idg 8946 TDZE 292 Apt Elev 341
--	------------------------	---

RNAV (GPS) RWY 27
MEMPHIS INTL (MEM)

RNP APCH - GPS.		 		MISSED APPROACH: Climb to 5000 direct AVADE and on track 279° to GOWRI and hold, continue climb-in-hold to 5000.	
 For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -9°C or above 54°C. For Inop ALS, increase LNAV Cat C and D visibility to 1½ SM.  *RVR 1800 authorized with use of FD or AP or HUD to DA.		 			
MEMPHIS APP CON		MEMPHIS TOWER		GND CON	
119.1	291.6 (176°-355°)	(Rwy 9-27)	118.3 257.8	(Rwy 9-27)	121.0 379.2
		(Rwys 18C-36C, 18L-36R)	119.7 257.8	(Rwys 18C-36C, 18L-36R)	121.9 379.2
125.8	338.3 (356°-175°)	(Rwy 18R-36L)	128.425 257.8	(Rwy 18R-36L)	121.65 379.2

D-ATIS 127.75		CLNC DEL 125.2	CPDLC
-------------------------	---	--------------------------	-------



CATEGORY	A	B	C	D
LPV DA *	492/24 200 (200-½)			
LNAV/VNAV DA	745/50 453 (500-1)			
LNAV MDA	800/24 508 (500-½)		800/55 508 (500-1)	
C CIRCLING	940-1 599 (600-1)		940-1½ 599 (600-½)	1020-2¼ 679 (700-2¼)