RNAV (RNP) Z RWY 22
LAGUARDIA (LGA)

APP CRS	Rwy ldg	7001
224°	TDZE	12
	Apt Elev	21

RNP AR APCH - GPS. RF required.

NA — For uncompensated Baro-VNAV systems, procedure NA below -11°C or above 54°C. For inop ALS, increase RNP 0.30 DA* visibility to RVR 5500.

ALSF-1

MISSED APPROACH: Climb to 3000 direct PROUD and hold, continue climb-in-hold to 3000. *Missed approach requires minimum climb of 397 feet per NM to 560.

D-ATIS ARR 125.95	NEW YORK APP CON	LAGUARDIA TOWER	GND CON	CLNC DEL	CPDLC
D-ATIS DEP 127.05	120.8 263.0	118.7 263.0	121.7 263.0	135.2	





CATEGORY	A	B	C	D
RNP 0.30 DA*	384/35 372 (400-⅝)			
RNP 0.30 DA	445/40 433 (500-¾)			

AUTHORIZATION REQUIRED



HIRL Rwys 4-22 and 13-31
REIL Rwy 31
TDZ/CL Rwys 4, 13, and 22

NE-2, 16 MAY 2024 to 13 JUN 2024
NE-2, 16 MAY 2024 to 13 JUN 2024