EL CENTRO, CALIFORNIA

RNAV (GPS) RWY 8

EL CENTRO NAF (VRACIU FLD) (KNJK)

WAAS CH 89932 W08A	APCH CRS 079°	Rwy ldg 9503 TDZE -46 Arpt Elev -42	- (USN)

RNP APCH

Circling visibility reduction by helicopters NA.
When tower closed, increase visibility to 1 mile.

MISSED APPROACH: Climb to 800, then climbing right turn to 2400 direct BEENY and hold.

ATIS★	APP CON/DEP CON	TOWER★	GND CON	CLNC DEL
269.275	128.55 292.2	119.1 360.2	121.9 254.35	340.2

Circling to Rwy 30 NA at night.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C (7°F) or above 54°C (129°F).

(IF) HOPSE 3600 2300
DRESR 2200
(FAF) BONII
-30 RW08
138
IMPERIAL COUNTY
4 NM
077°
257°
BEENY
JADOL
2300
062° (3.6)
2200
079° (2)
1600 (3)
3500
049° (5.9)
(IAF) KUMBA 4000
1000
3000
MSA RW08 25 NM
6700
UNITED STATES
MEXICO
4581
EMERG SAFE ALT 100 NM 17,000

800 crs 079°
2400
BEENY

HOPSE
3600 2300
079°
DRESR
2200
BONII
RW08
1600
GP 3.00°
TCH 50
5 NM

ELEV -42
TDZE -46

079°
12
9503 x 200
26
6825 x 200
TWR
H
138
30

CATEGORY	A	B	C	D
LPV DA	204-¾ 250 (300-¾)			
LNAV/VNAV DA	204-¾ 250 (300-¾)	235-⅞ 281 (300-⅞)	249-⅞ 295 (300-⅞)	268-⅞ 314 (400-⅞)
LNAV MDA	460-1 506 (600-1)		460-1⅜ 506 (600-1⅜)	
C CIRCLING	480-1 522 (600-1)		480-1½ 522 (600-1½)	520-2 562 (600-2)

HIRL Rwys 8-26, 12-30

SW-3, 18 APR 2024 to 16 MAY 2024
SW-3, 18 APR 2024 to 16 MAY 2024