

SBAS Chan 62106 W21A	APCH CRS 215°	Rwy Idg 10,995 TDZE 58 Arpt Elev 63
--	-------------------------	--

ILS or LOC or RNAV (GPS) RWY 21L

[USAF]

TRAVIS AFB (KSUU)

RNP APCH. RNAV1-GPS or RADAR required for ILS, LOC.

RADAR required for CAT E aircraft for full procedure off of SEATO.


- ▼
- * When ALS inop, increase RVR to 40, vis to ¾ miles.
 - ** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE vis to 1¾ miles.
 - ***Circling not authorized NW of Rwy 3L-21R.




MISSED APPROACH: Climb to 2200 then climbing right turn to 4500 direct SEATO and hold, continue climb in hold to 4500.

ATIS 135.55 292.125	APP CON 119.9 322.325 (S) 126.6 281.45 (N)	TOWER 120.75 254.4	GND CON 121.8 289.4	CLNC DEL 127.55 335.8
-------------------------------	--	------------------------------	-------------------------------	---------------------------------


† When TDZ/CL inop, increase RVR to 24, RVR 18 authorized use of FD or AP or HUD to DA.



EMERG SAFE ALT 100 NM 13,000



CATEGORY	A	B	C	D	E
S-ILS 21L**†	258/18		200	(200-½)	
LPV DA**†	258/18		200	(200-½)	
S-LOC 21L**	500/24	442 (500-½)	500/45	442 (500-¾)	
RNAV MDA**	500/24	442 (500-½)	500/45	442 (500-¾)	
CIRCLING***	560-1 497 (500-1)	660-1 597 (600-1)	1100-3 1037(1100-3)	1200-3	1137 (1200-3)



ILS or LOC or RNAV (GPS) RWY 21L

SW-2, 18 APR 2024 to 16 MAY 2024

SW-2, 18 APR 2024 to 16 MAY 2024