

ILS or LOC RWY 22

LOC I-CVS <u>109.7</u>	APCH CRS <u>218°</u>	Rwy Idg 10,003 TDZE 4295 Arprt Elev 4295	AL-512 [USAF]	CANNON AFB (KCVS)
----------------------------------	--------------------------------	---	---------------	-------------------

▼ * When ALS inop, increase RVR to 40 and vis to $\frac{3}{4}$ miles.
 ** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile,
 CAT CDE vis to $1\frac{1}{4}$ miles.

ATIS 119.1 269.9	CANNON APP CON 118.425 352.1	CANNON TOWER 120.4 270.25	GND CON 121.9 275.8	CLNC DEL 120.2 293.225
----------------------------	--	-------------------------------------	-------------------------------	----------------------------------

CAUTION:
 1. ILS Rwy 22 Height Group 4 WCH 19 feet.

† Missed approach requires use of RNAV or ATC RADAR monitoring.

ELEV 4295		TDZE 4295	
6000 CVS R-220	JEBES CVS R-220 [6]	7000	CLINK CVS R-193 [12]
EMERG SAFE ALT 100 NM 8000			
TACAN LOC MAP [1.2] 4 NM [2.4] 5600 OPKUE CVS [5.1] HEDOB R-003 [12] HEKDI [12] Arc [12] GS 3.00° TCH 44			
CATEGORY	A	B	E
S-ILS 22*	4495/24		
S-LOC 22**	4720/24 425 (500-½)	4720/40 425 (500-¾)	
C CIRCLING	4840-1 545 (600-1)	4860-1½	5000-2¼
		565 (600-1½)	705 (800-2¼)
		5020-2½	725 (800-2½)

FAF to MAP 4 NM				
Knots	60	90	120	150
Min:Sec	4:00	2:40	2:00	1:36