

WAAS CH 60922 W13A	APP CRS 128°	Rwy Idg TDZE 632 Apt Elev 661	9604 632 661
--	------------------------	---	---

RNAV (GPS) RWY 13

GENERAL DOWNING-PEORIA INTL (PIA)


RNP APCH - GPS

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. When local altimeter setting not received, use Lincoln altimeter setting increase LPV DA to 1110 feet and all visibilities ¼ SM. Increase LNAV/VNAV DA to 1168 feet and all visibilities ½ SM. Increase all MDAs 100 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ½ SM. Baro-VNAV and VDP NA when using Lincoln altimeter setting. For inop ALS, increase LPV all Cats visibility to 1½ SM, LNAV Cat A/B visibility to 1 SM and Cat C/D visibility to 1½ SM. For inop ALS when using Lincoln altimeter setting, increase LPV visibility all Cats to 1½ SM and LNAV Cat A/B visibility to 1 SM.

MALSR

MISSED APPROACH:
Climb to 2400 direct CASIP and hold.

ATIS 126.1 282.2	SAINT LOUIS APP CON 125.8 269.2	PEORIA TOWER 124.0 353.85	GND CON 121.85 348.6
----------------------------	---	-------------------------------------	--------------------------------



VGS and RNAV glidepath not coincident (VGS Angle 3.00/TCH 57).				2400	CASIP
4 NM Holding Pattern				2500	
GP 3.00° TCH 59				2500	
FAPSA				EPEPE	
2500 ← 308° → 128° → 2500				1.3 NM to RW13	
6 NM				4.3 NM	
CATEGORY				1.3	
LPV DA				A	B
LNAV/VNAV DA				C	D
LNAV MDA				1120-½	484 (500-½)
CIRCLING				1160-1	499 (500-1)

