

LOC I-RIW <u>110.5</u>	APP CRS 284°	Rwy Idg TDZE Apt Elev	8204 5459 5516
----------------------------------	------------------------	-----------------------------	---

ILS or LOC RWY 28
CENTRAL WYOMING RGNL (RIW)

T When local altimeter setting not received, use Lander altimeter setting: increase
A NA DA to 5713 feet; increase all MDA 60 feet and S-LOC 28 Cat C and D visibility
 ¼ mile. For Inop MALSR, when using Lander altimeter setting, increase S-ILS 28
 all Cts visibility to ¾ mile and S-LOC 28 Cat C and D visibility to 1¾ mile.
 VDP NA when using Lander altimeter setting.

MALSR



MISSED APPROACH: Climb to 6800 then climbing right turn to 7700 direct RIW VOR/DME and hold, continue climb-in-hold to 7700.

ASOS	SALT LAKE CENTER	UNICOM
121.425	133.25 285.6	122.8 (CTAF) 0

(IAF)
FETIK
RIW 14

BOYSEN RESERVOIR
117.8 BOY 
Chan 125

LOCALIZER 110.5
I-RW

5724



RIVERTON
114.05 RW :--
Chan 87(Y)

ELEV 5516		TDZE 5459
-----------	---	-----------

REIL Rwyys 1, 10 and 19 L

MIRL Rwy 1-19

HIRE Rwy 10-28

FAF to MAP 6.9 NM

Knots	60	90	120	150	180
Min:Sec	6:54	4:36	3:27	2:46	2:18

RIVERTON, WYOMING

Amdt 3B 07SEP23

43°04'N-108°28'W

CENTRAL WYOMING RGNL (RIW)

ILS or LOC RWY 28

NW-1, 18 APR 2024 to 16 MAY 2024

NW-1, 18 APR 2024 to 16 MAY 2024