

MAYPORT, FLORIDA

COPTER RNAV (GPS) RWY 23

WAAS CH 45485 W23B	APCH CRS 229°	Rwy ldg TDZE Arpt Elev	8001 15 15
--------------------------	------------------	------------------------------	------------------

AL-722 (USN)

MAYPORT NS (ADM DAVID L MC DONALD FLD) (KNRB)

⚠ * LPV and LNAV/VNAV procedures are authorized only when the St. Johns River is clear of vessels from the mouth of Haulover Creek to St. Johns Point. ATC will advise aircraft on final approach if a conflict is present and coordinate a missed approach as required. Does not apply to practice approaches in VMC. Visibility Reduction by Helicopters NA.	MISSED APPROACH: Climb to 600 then climbing left turn to 1500 direct to CONWY and hold.
---	--

ATIS★ 236.775	JACKSONVILLE APP CON/DEP CON 124.9 308.4	TOWER★ 118.75 239.3	GND CON 126.5 233.7	ASR/PAR
------------------	---	------------------------	------------------------	---------

RNP APCH

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.

Max airspeed 90 KIAS.

This approach is not authorized at night when the VGSI is inop, unless the St. Johns River is clear of vessels from the mouth of Haulover Creek to St. Johns Point. ATC will advise aircraft on final approach if a conflict is present and coordinate a missed approach as required.

CAUTION: Vessels with masts up to 150' transitioning the St. Johns River inside of NRB 2 DME.

MSA RW23 25 NM

RADAR REQUIRED

EMERG SAFE ALT 100 NM 2800

600

crs 229°

1500

CONWY

CATEGORY	COPTER		
LPV DA*	319-1	304	(400-1)
LNAV/VNAV DA*	385-1	370	(400-1)
LNAV MDA	520-1	505	(600-1)
CIRCLING	560-1	545	(600-1)

ELEV 15

TDZE 15

MAYPORT, FLORIDA

30°23'N - 81°25'W MAYPORT NS (ADM DAVID L MC DONALD FLD) (KNRB)

Orig 24MAR22

COPTER RNAV (GPS) RWY 23

SE-3, 16 MAY 2024 to 13 JUN 2024

SE-3, 16 MAY 2024 to 13 JUN 2024